

Carefree™

Standard Sand Filter Systems are designed and equipped to offer the ideal combination of energy efficient, trouble-free operation and crystal clear, sparkling water.

Features:

- Large sand filter bodies for extra-long filtering cycles and heavy-duty capacity
- Each system is designed for quick assembly and precise alignment of components
- Pump and filter performance matched to provide optimum flow and energy efficiency
- 7-position, threaded multi-port valve is easy to use and install
- Hi-Flo high performance single and dual speed pump
- All the hoses, fittings and clamps needed for installation
- Standard one-piece pump and filter mounting base



2-Speed

Part No.	Filter	Filtration	Flow Rate	Pump	HP	6 Hr. Turnover	8 Hr. Turnover
522-5300-6S	16"	1.4 sq. ft.	35 GPM	PH2100-6	1.0	12,600 gal.	16,800 gal.
522-5320-6S	19"	2.0 sq. ft.	45 GPM	PH2100-6	1.0	16,200	21,600
522-5330-6S	19"	2.0 sq. ft.	45 GPM	PH2150-6	1.5	16,200	21,600
522-5350-6S	22"	2.6 sq. ft.	55 GPM	PH2100-6	1.0	19,800	26,400
522-5340-6S	22"	2.6 sq. ft.	55 GPM	PH2150-6	1.5	19,800	26,400

6 ft. cord, regular (NEMA) plug. Change (-6) on part number to (-3) for 3 ft. cord twist-lock plug. Pumps are 2-speed.

1-Speed

Part No.	Filter	Filtration	Flow Rate	Pump	HP	6 Hr. Turnover	8 Hr. Turnover
520-5300-6S	16"	1.4 sq. ft.	35 GPM	PH1100-6	1.0	12,600 gal.	16,800 gal.
520-5320-6S	19"	2.0 sq. ft.	45 GPM	PH1100-6	1.0	16,200	21,600
520-5330-6S	19"	2.0 sq. ft.	45 GPM	PH1150-6	1.5	16,200	21,600
520-5350-6S	22"	2.6 sq. ft.	55 GPM	PH1100-6	1.0	19,800	26,400
520-5340-6S	22"	2.6 sq. ft.	55 GPM	PH1150-6	1.5	19,800	26,400

6 ft. cord, regular (NEMA) plug. Change (-6) on part number to (-3) for 3 ft. cord twist-lock plug. Pumps are 1-speed.



2200 East Sturgis Road, Oxnard, California 93030 • Ph. 805-981-0262 • Fax 805-981-9403
 waterway@waterwayplastics.com • www.waterwayplastics.com




Carefree Series Filters and Hi-Flo Pumps are also available as individual units to custom design filtration requirements for new or existing pools. Choose the appropriate pump as well as system enhancing accessories, such as optional automatic pump timer and chlorine feeders.


Standard Sand Filter Systems

Specifications


Filter type:	High-Rate Sand: No. 20 Silica
Filter tank:	Roto-Molded Polymeric
Underdrain:	360° self-cleaning, slotted laterals - threaded for ease of maintenance
Control Valve:	7-position, top-mount, multi-port with lever-action handle
Valve Fastening:	Split-nut thread design
Pump & Motor:	Hi-Flo Series pump - 115 volts
Mounting Base:	Molded thermoplastic




This economical system will provide crystal Carefree water with minimal maintenance for smaller above-ground pools.



A large system that is designed for most above ground pools



A high-powered, high-capacity system that will provide years of maintenance-free swimming pool filtration for larger above ground pools



The ultimate sand filter system for large above ground pools and small in-ground pools.

The Hi-Flo Pump was designed for superior and efficient performance. This pump features high flow rate performance for faster filtering cycles. The Hi-Flo is ideal for new installations or as a replacement pump.

Features:

- 1 1/2" Union threads / 1 1/2" FPT Intake
- 2" Union threads / 1 1/2" FPT discharge
- Large 6" pump trap with clear lid
- Powerful side discharge performance
- Wet end rotates for easy installation



**LISTED
(SWIMMING POOL
OR SPA PUMP)
7J06**



2200 East Sturgis Road, Oxnard, California 93030 • Ph. 805-981-0262 • Fax 805-981-9403
waterway@waterwayplastics.com • www.waterwayplastics.com

