

HYDRAPOOOLS

INGROUND LINER INSTALLATION INSTRUCTIONS

1. This installation page is a brief outline of what needs to be done when installing a vinyl liner. For further information regarding liner installation refer to your complete pool installation manual or contact your local dealer.
2. Tape all seams where panels join in the pool to secure good vacuum suction; tape returns and between liner receptor and wall.
3. Broom sweep and/or vacuum hard bottom of any foreign objects (dirt, pebbles, etc.)
4. Secure bottom main drain gasket to main drain.
5. You are now ready to install the liner. Vinyl liners are best installed in warm sunny weather.
6. Carefully place carton in shallow end with arrows pointing toward shallow end.
7. Remove liner from carton. Open liner across width of pool.
8. Shallow end material will be on top of the folded line.
9. Install beading into liner receptor around shallow end first. Set shallow end and sand bag against step and break. Install the bead for the deep end. "Deep End" stamp should be in the deep end of the pool. Corners should be marked with tape too.
10. Set up vacuum and help liner into position.
11. **"Important Note"**-do not cut main drain, skimmer, stair, or returns until completely satisfied with liner fit.
12. Where fiberglass walk-in stairs are involved, stair area must be sealed off (tape back of liner to stairs), or seal top of stair with $\frac{3}{4}$ " plywood; tape around edge; secure liner edge to plywood.
13. Only if satisfied with the liner fit, and when 1'6" of water has filled in the deep end, secure main drain faceplate.
14. Leave vacuum running continually until 1'0" of water is in the shallow end.
15. At this point, the vacuum may be shut off and the hose removed from behind the liner.
16. Do not install the outlet and skimmer faceplates until water reaches 1" below bottom outlets and skimmer.
17. **IT IS THE RESPONSIBILITY OF THE POOL OWNER TO PROPERLY RE-INSTALL THE REPLACEMENT OF THE ROPE ANCHOR DEVICES AND THE ROPE AND FLOAT ASSEMBLY FOLLOWING THE INSTALLATION OF THE LINER.**
18. Never drain the pool without consulting a pool dealer.
19. Improper installation of liner may void the liner warranty.