

THE COMPLETE LINE OF D.O.E. APPROVED PUMPS



Power Defender
Variable Speed Pumps
are Energy Star Approved!



IN-GROUND PUMPS

Model #	Total HP	Description	WEF (Weighted Energy Factor)
PD-270	2.7	2.7 THP, Variable Speed	7.253
PD-270A	2.7	2.7 THP, Variable Speed SVL	7.716
PD-225	2.25	2.25 THP, Variable Speed	7.460
PD-165	1.65	1.65 THP, Variable Speed, Dual Voltage	7.796
PD-140	1.4	1.4 THP, Variable Speed, Dual Voltage	9.58
PD-140C	1.4	1.4 THP, Variable Speed, Dual Voltage with Valve Control	9.58
SMF-107	0.95	.95 THP, Single Speed	4.11
WB075	1.25	1.25 THP, Booster Pump	.502

ABOVE GROUND PUMPS

PD-140ABG	1.4	1.4 THP, Variable Speed, Dual Voltage	10.295
CD-07-1-N	0.75	.75 THP, Center Discharge, with 3' NEMA Cord	3.887
CD-07-1-T	0.75	.75 THP, Center Discharge, with 3' Twist Lock Cord	3.887
CD-10-1-N	0.95	.95 THP, Center Discharge, with 3' NEMA Cord	3.632
CD-10-1-T	0.95	.95 THP, Center Discharge, with 3' Twist Lock Cord	3.632
CP-1/8-1N11A	0.125	1/8 THP, with 3' NEMA Cord	10.863
SD-07-1-N*	0.75	3/4 THP, Hi-Flo II, Side Discharge, with 3' NEMA Cord	3.99
SD-07-1-T*	0.75	3/4 THP, Hi-Flo II, Side Discharge, with 3' Twist Lock Cord	3.99
SD-10-1-N*	0.95	.95 THP, Hi-Flo II, Side Discharge, with 3' NEMA Cord	3.759
SD-10-1-T*	0.95	.95 THP, Hi-Flo II, Side Discharge, with 3' Twist Lock Cord	3.759
SD-07-2-N*	0.75	.75 THP, 2-Speed Hi-Flo II, Side Discharge, with 3' NEMA Cord	6.158
SD-07-2-T*	0.75	.75 THP, 2-Speed Hi-Flo II, Side Discharge, with 3' Twist Lock Cord	6.158
SD-10-2-N*	1	1 THP, 2-Speed Hi-Flo II, Side Discharge, with 3' NEMA Cord	6.059
SD-10-2-T*	1	1 THP, 2-Speed Hi-Flo II, Side Discharge, with 3' Twist Lock Cord	6.059

*NOTE: For Horizontal Hi Flo II, need to add a "- H" at the end of the above Hi Flo II part numbers.



Designed, Engineered &
Manufactured in the USA.